



# TruLaser Tube 5000 fiber

Technical data



## TruLaser Tube 5000 fiber

### ROUND TUBE

MAXIMUM OUTSIDE DIAMETER	152 mm
MAXIMUM OUTSIDE DIAMETER (OPTIONAL)	170 mm <sup>1</sup>

### RECTANGULAR PROFILE

MAXIMUM SIDE LENGTH AND OUTER CIRCLE DIAMETER	152 mm / 170 mm
MAXIMUM SIDE LENGTH AND OUTER CIRCLE DIAMETER (OPTIONAL)	180 mm / 180 mm <sup>2</sup>

### MAXIMUM RAW MATERIAL LENGTH FOR AUTOMATIC LOADING

FOR LOADMASTER TUBE 6.5 M	6500 mm
FOR LOADMASTER TUBE 8.0 M	8000 mm <sup>3</sup>

### FINISHED PART LENGTH

FOR UNLOADING UNIT 3 M	3000 mm
FOR UNLOADING UNIT 3 M + 1.5 M	4500 mm <sup>3</sup>
FOR UNLOADING UNIT 6.5 M	6500 mm <sup>3</sup>
FOR UNLOADING UNIT 6.5 M + 1.5 M	8000 mm <sup>3</sup>

### WORKPIECE WEIGHT

MAXIMUM PATH WEIGHT (STANDARD/OPTIONAL)	25 kg/m
---	---------

### MAXIMUM RAW MATERIAL WEIGHT WITH AUTOMATIC LOADING

WITH LOADMASTER TUBE 6.5 M	162.5 kg
WITH LOADMASTER TUBE 8.0 M	200 kg

Subject to changes. The details in our offer and order confirmation are definitive.



Footnotes

---

1 — Round tubes with a diameter of 152 mm to 170 mm can only be manually loaded.

2 — Rectangular profiles with a side length of >152.4 mm can only be manually loaded

3 — Value for extended versions (option)