



# TruTool TKF 1101

Technical data

**TruTool TKF 1101 30°  
bevel angle****TruTool TKF 1101  
37.5° bevel angle****TruTool TKF 1101 45°  
bevel angle****MAXIMUM CHAMFER LENGTHS**MAXIMUM CHAMFER LENGTH,  
STEEL 400 N/MM<sup>2</sup>

11 mm

11 mm

11 mm

MAXIMUM CHAMFER LENGTH,  
STEEL 600 N/MM<sup>2</sup>

9 mm

9 mm

9 mm

MAXIMUM CHAMFER LENGTH,  
STEEL 800 N/MM<sup>2</sup>

6 mm

6 mm

6 mm

**RADII**

SMALLEST RADIUS

40 mm

40 mm

40 mm

**GENERAL**

WORKING SPEED

2 m/min

2 m/min

2 m/min

STROKE RATE AT NOMINAL LOAD

340 / 440 1/min

340 / 440 1/min

340 / 440 1/min

NOMINAL POWER CONSUMPTION

1600 W

1600 W

1600 W

SHEET THICKNESS

3 mm - 25 mm

3 mm - 25 mm

3 mm - 25 mm

**WEIGHT**

WEIGHT WITHOUT CABLE

10 kg

10 kg

10 kg

---

Subject to changes. The information in our offer and our order confirmation is definitive.