



# TruTool N 160 with extension, Li-ion

Technical data

**MAXIMUM SHEET THICKNESSES**

|   |        |
|---|--------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM <sup>2</sup>          | 1.6 mm |
| MAXIMUM SHEET THICKNESS, STEEL 600 N/MM <sup>2</sup>          | 1 mm   |
| MAXIMUM SHEET THICKNESS, STEEL 800 N/MM <sup>2</sup>          | 0.7 mm |
| MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM <sup>2</sup> | 2 mm   |

**RADI**

|                 |       |
|-----------------|-------|
| SMALLEST RADIUS | 24 mm |
|-----------------|-------|

**GENERAL**

|                             |            |
|-----------------------------|------------|
| WORKING SPEED               | 1.9 m/min  |
| STROKE RATE AT NOMINAL LOAD | 2070 1/min |
| STARTING HOLE DIAMETER      | 22 mm      |
| VOLTAGE                     | 10.8 V     |

**WEIGHT**

|   |        |
|---|--------|
| WEIGHT (WITH 2 AH RECHARGEABLE BATTERY) | 1.7 kg |
| WEIGHT (WITH 4 AH RECHARGEABLE BATTERY) | 1.8 kg |