



TruTool S 114 12V LiHD rechargeable battery

Technical data

TruTool S 114 12V LiHD rechargeable battery

MAXIMUM SHEET THICKNESSES

| | |
|---------------------------------------------------------------|-------------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM ² | 1.6 mm |
| MAXIMUM SHEET THICKNESS, STEEL 600 N/MM ² | 1 mm |
| MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM ² | 2 mm |
| SPIRAL DUCT, STEEL 400 N/MM ² | 4 x 0,75 mm |
| SPIRAL DUCT, STEEL 600 N/MM ² | 4 x 0,5 mm |

RADII

| | |
|-----------------|-------|
| SMALLEST RADIUS | 60 mm |
|-----------------|-------|

GENERAL

| | |
|-----------------------------|--------------------|
| WORKING SPEED | 6 m/min - 13 m/min |
| STROKE RATE DURING IDLE RUN | 5500 1/min |
| VOLTAGE | 12 V |
| MINIMUM TUBE DIAMETER | 50 mm |
| THROAT DEPTH | 30 mm |

WEIGHT

| | |
|-----------------------------------------|--------|
| WEIGHT (WITH 4 AH RECHARGEABLE BATTERY) | 1.8 kg |
|-----------------------------------------|--------|