



# TruBend Series 5000

Technical data



**TruBend 5085****TruBend 5085 (S)****TruBend 5130**

<b>PRESS FORCE</b>	850 kN	850 kN	1300 kN
<b>BENDING LENGTH</b>	2210 mm	2720 mm	3230 mm
<b>WIDTH BETWEEN COLUMNS</b>	1750 mm	2260 mm	2690 mm
<b>USABLE OPEN HEIGHT</b>	385 mm	615 mm	385 mm
<b>USABLE OPEN HEIGHT FOR EXTENDED VERSION (OPTION)</b>	615 mm	-	615 mm
<b>THROAT DEPTH</b>	420 mm	420 mm	420 mm
<b>USER INTERFACE</b>	Touchpoint TruBend	Touchpoint TruBend	Touchpoint TruBend
<b>MAXIMUM SPEED Y AXIS, OPERATION (OPTION)</b>	25 mm/s	25 mm/s	25 mm/s
<b>DIMENSIONS, WEIGHTS</b>			
LENGTH	3020 mm	3530 mm	3980 mm
WIDTH	1800 mm	1800 mm	1900 mm
HEIGHT	2840 mm	2840 mm	2840 mm
WEIGHT	8300 kg	9100 kg	11800 kg

**TruBend 5170****TruBend 5170 (S)****TruBend 5230**

<b>PRESS FORCE</b>	1700 kN	1700 kN	2300 kN
<b>BENDING LENGTH</b>	3230 mm	4250 mm	3230 mm
<b>WIDTH BETWEEN COLUMNS</b>	2690 mm	3680 mm	2690 mm
<b>USABLE OPEN HEIGHT</b>	615 mm	615 mm	615 mm
<b>USABLE OPEN HEIGHT FOR EXTENDED VERSION (OPTION)</b>	-	-	-
<b>THROAT DEPTH</b>	420 mm	420 mm	420 mm
<b>USER INTERFACE</b>	Touchpoint TruBend	Touchpoint TruBend	Touchpoint TruBend
<b>MAXIMUM SPEED Y AXIS, OPERATION (OPTION)</b>	25 mm/s	25 mm/s	25 mm/s
<b>DIMENSIONS, WEIGHTS</b>			
LENGTH	3980 mm	4970 mm	4150 mm
WIDTH	1900 mm	1900 mm	2055 mm
HEIGHT	3000 mm	3000 mm	3000 mm
WEIGHT	14150 kg	17850 kg	17200 kg

**TruBend 5230 (S)****TruBend 5320**

<b>PRESS FORCE</b>	2300 kN	3200 kN
--------------------	---------	---------

**TruBend 5230 (S)****TruBend 5320**

**BENDING LENGTH** 4250 mm 4420 mm

**WIDTH BETWEEN COLUMNS** 3680 mm 3680 mm

**USABLE OPEN HEIGHT** 615 mm 615 mm

**USABLE OPEN HEIGHT FOR EXTENDED VERSION (OPTION)** - -

**THROAT DEPTH** 420 mm 420 mm

**USER INTERFACE** Touchpoint TruBend Touchpoint TruBend

**MAXIMUM SPEED Y AXIS, OPERATION (OPTION)** 25 mm/s 25 mm/s

**DIMENSIONS, WEIGHTS**

LENGTH 5140 mm 5180 mm

WIDTH 2055 mm 2055 mm

HEIGHT 3000 mm 3200 mm

WEIGHT 19850 kg 23400 kg