



TruLaser Tube 5000 fiber

Technical data

TruLaser Tube 5000 fiber

ROUND TUBE

MAX. OUTSIDE DIAMETER	152 mm
MAX. OUTSIDE DIAMETER (OPTIONAL)	170 mm ¹

RECTANGULAR PROFILE

MAX. SIDE LENGTH AND OUTER CIRCLE DIAMETER	152 mm / 170 mm
--	-----------------

MAX. RAW MATERIAL LENGTH FOR AUTOMATIC LOADING

FOR LOADMASTER TUBE 6.5 M	6500 mm
FOR LOADMASTER TUBE 8.0 M	8000 mm ²

FINISHED PART LENGTH

FOR UNLOADING UNIT 3 M	3000 mm
FOR UNLOADING UNIT 3 M + 1.5 M	4500 mm ²
FOR UNLOADING UNIT 6.5 M	6500 mm ²
FOR UNLOADING UNIT 6.5 M + 1.5 M	8000 mm ²

WORKPIECE WEIGHT

MAX. PATH WEIGHT (STANDARD/OPTIONAL)	20 kg/m / - kg/m
--------------------------------------	------------------

MAX. RAW MATERIAL WEIGHT WITH AUTOMATIC LOADING

WITH LOADMASTER TUBE 6.5 M	130 kg
WITH LOADMASTER TUBE 8.0 M	160 kg

LASER-SPECIFIC DATA - TRUDISK 2001

MAX. LASER OUTPUT	2000 W
MAX. MATERIAL THICKNESS, MILD STEEL	8 mm
MAX. MATERIAL THICKNESS, STAINLESS STEEL	4 mm
MAX. MATERIAL THICKNESS, ALUMINUM	2 mm
MAX. MATERIAL THICKNESS, COPPER	3 mm
MAX. MATERIAL THICKNESS, BRASS	3 mm

LASER-SPECIFIC DATA - TRUDISK 3001

MAX. LASER OUTPUT	3000 W
MAX. MATERIAL THICKNESS, MILD STEEL	8 mm
MAX. MATERIAL THICKNESS, STAINLESS STEEL	5 mm
MAX. MATERIAL THICKNESS, ALUMINUM	6 mm
MAX. MATERIAL THICKNESS, COPPER	4 mm
MAX. MATERIAL THICKNESS, BRASS	4 mm

CONSUMPTION VALUES - TRUDISK 2001

AVERAGE POWER INPUT IN PRODUCTION	8 kW
-----------------------------------	------

CONSUMPTION VALUES - TRUDISK 3001

AVERAGE POWER INPUT IN PRODUCTION	9 kW
-----------------------------------	------

Subject to changes. The information in our offer and our order confirmation is definitive.

Footnotes

1 — Round tubes with a diameter of 152 mm to 170 mm can only be manually loaded.

2 — Value for extended versions (option)