



# TruPulse nano

Technical data

**TruPulse 1002 nano  
(FK10-EP)****TruPulse 1002 nano  
(FK10-HS)****TruPulse 1003 nano  
(FK10-HS)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	20 W	20 W	30 W
MAXIMUM PEAK PULSE POWER	> 7 kW	> 7 kW	> 7 kW
BEAM QUALITY (M <sup>2</sup> )	< 1.3	< 1.3	< 1.3
WAVELENGTH	1062 nm ± 3 nm	1062 nm ± 3 nm	1062 nm ± 3 nm
MAXIMUM PULSE ENERGY	> 0.6 mJ	> 0.6 mJ	> 0.6 mJ
PULSE DURATION RANGE	3 ns - 500 ns	10 ns - 240 ns	10 ns - 240 ns
PULSE REPETITION FREQUENCY	1 kHz - 1000 kHz	1 kHz - 1000 kHz	1 kHz - 1000 kHz
WAVELENGTH SPECTRUM			

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

**INSTALLATION**

AMBIENT TEMPERATURE	0 °C - 45 °C	0 °C - 45 °C	0 °C - 45 °C
---------------------	--------------	--------------	--------------

**TruPulse 1005 nano  
(FK10-HS)****TruPulse 1010 nano  
(FK10-EP)****TruPulse 2002 nano  
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	50 W	100 W	20 W
MAXIMUM PEAK PULSE POWER	> 7 kW	> 7 kW	> 10 kW
BEAM QUALITY (M <sup>2</sup> )	< 1.3	< 1.3	< 1.6
WAVELENGTH	1062 nm ± 3 nm	1062 nm ± 3 nm	1062 nm ± 3 nm
MAXIMUM PULSE ENERGY	> 0.6 mJ	> 1 mJ	> 1 mJ
PULSE DURATION RANGE	11 ns - 220 ns	4 ns - 2000 ns	3 ns - 500 ns
PULSE REPETITION FREQUENCY	1 kHz - 1000 kHz	1 kHz - 4000 kHz	1 kHz - 1000 kHz
WAVELENGTH SPECTRUM			

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	377 mm x 249 mm x 115 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	--------------------------	-------------------------

**INSTALLATION**

AMBIENT TEMPERATURE	0 °C - 42 °C	5 °C - 40 °C	0 °C - 45 °C
---------------------	--------------	--------------	--------------

**TruPulse 2002 nano  
(FK10-RM)****TruPulse 2003 nano  
(FK10-RM)****TruPulse 2005 nano  
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	20 W	30 W	50 W
MAXIMUM PEAK PULSE POWER	> 10 kW	> 10 kW	> 10 kW
BEAM QUALITY (M <sup>2</sup> )	< 1.6	< 1.6	< 1.6
WAVELENGTH		1062 nm ± 3 nm	1062 nm ± 3 nm
MAXIMUM PULSE ENERGY	> 1 mJ	> 1 mJ	> 1 mJ

**TruPulse 2002 nano  
(FK10-RM)****TruPulse 2003 nano  
(FK10-RM)****TruPulse 2005 nano  
(FK10-EP)**

PULSE DURATION RANGE	26 ns - 250 ns	26 ns - 250 ns	6 ns - 500 ns
PULSE REPETITION FREQUENCY	1 kHz - 500 kHz	1 kHz - 500 kHz	1 kHz - 1000 kHz
WAVELENGTH SPECTRUM	1059 nm - 1065 nm		

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

**INSTALLATION**

AMBIENT TEMPERATURE	0 °C - 45 °C	0 °C - 45 °C	0 °C - 40 °C
---------------------	--------------	--------------	--------------

**TruPulse 2005 nano  
(FK10-RM)****TruPulse 2007 nano  
(FK10-EP)****TruPulse 2007 nano  
(FK10-RM)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	50 W	70 W	70 W
MAXIMUM PEAK PULSE POWER	> 10 kW	> 10 kW	> 10 kW
BEAM QUALITY (M <sup>2</sup> )	< 1.6	< 1.6	< 1.6
WAVELENGTH	1062 nm ± 3 nm	1062 nm ± 3 nm	1062 nm ± 3 nm
MAXIMUM PULSE ENERGY	> 1 mJ	> 1 mJ	> 1 mJ
PULSE DURATION RANGE	26 ns - 250 ns	9 ns - 500 ns	28 ns - 260 ns
PULSE REPETITION FREQUENCY	1 kHz - 500 kHz	1 kHz - 1000 kHz	1 kHz - 500 kHz
WAVELENGTH SPECTRUM			

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	377 mm x 249 mm x 95 mm	377 mm x 249 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

**INSTALLATION**

AMBIENT TEMPERATURE	0 °C - 40 °C	0 °C - 40 °C	0 °C - 40 °C
---------------------	--------------	--------------	--------------

**TruPulse 2010 nano  
(FK10-EP)****TruPulse 2013 nano  
(FK10-EP)****TruPulse 2020 nano  
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	100 W	130 W	200 W
MAXIMUM PEAK PULSE POWER	> 10 kW	> 10 kW	> 10 kW
BEAM QUALITY (M <sup>2</sup> )	< 1.6	< 1.6	< 1.6
WAVELENGTH	1062 nm ± 3 nm	1062 nm ± 3 nm	
MAXIMUM PULSE ENERGY	> 1.3 mJ	> 1.5 mJ	> 1.5 mJ
PULSE DURATION RANGE	4 ns - 2000 ns	3 ns - 2000 ns	9 ns - 2000 ns
PULSE REPETITION FREQUENCY	1 kHz - 4000 kHz	1 kHz - 4000 kHz	1 kHz - 4000 kHz
WAVELENGTH SPECTRUM			1059 nm - 1065 nm

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)	377 mm x 249 mm x 115 mm	423 mm x 417 mm x 133 mm	423 mm x 417 mm x 133 mm
------------------------	--------------------------	--------------------------	--------------------------

**INSTALLATION**

**TruPulse 2010 nano  
(FK10-EP)****TruPulse 2013 nano  
(FK10-EP)****TruPulse 2020 nano  
(FK10-EP)**

AMBIENT TEMPERATURE

0 °C - 40 °C

10 °C - 45 °C

10 °C - 40 °C

**TruPulse 3002 nano  
(FK10-EP)****TruPulse 3002 nano  
(FK10-HS)****TruPulse 4007 nano  
(FK10-HS)****LASER PARAMETERS**

AVERAGE OUTPUT POWER

20 W

20 W

70 W

MAXIMUM PEAK PULSE POWER

&gt; 12 kW

&gt; 12 kW

&gt; 20 kW

BEAM QUALITY (M<sup>2</sup>)

&lt; 1.8

1.8

3

WAVELENGTH

1062 nm ± 3 nm

1062 nm ± 3 nm

1062 nm ± 3 nm

MAXIMUM PULSE ENERGY

&gt; 1 mJ

&gt; 0.8 mJ

&gt; 1.25 mJ

PULSE DURATION RANGE

10 ns - 220 ns

2 ns - 500 ns

10 ns - 250 ns

PULSE REPETITION FREQUENCY

1 kHz - 1000 kHz

1 kHz - 1000 kHz

1 kHz - 1000 kHz

WAVELENGTH SPECTRUM

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)

347 mm x 201 mm x 95 mm

347 mm x 201 mm x 95 mm

377 mm x 249 mm x 95 mm

**INSTALLATION**

AMBIENT TEMPERATURE

0 °C - 45 °C

0 °C - 45 °C

0 °C - 40 °C

**TruPulse 5020 nano (FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER

200 W

MAXIMUM PEAK PULSE POWER

&gt; 50 kW

BEAM QUALITY (M<sup>2</sup>)

&lt; 5

WAVELENGTH

1062 nm ± 3 nm

MAXIMUM PULSE ENERGY

&gt; 5 mJ

PULSE DURATION RANGE

12 ns - 2000 ns

PULSE REPETITION FREQUENCY

1 kHz - 4000 kHz

WAVELENGTH SPECTRUM

**STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)

473 mm x 417 mm x 133 mm

**INSTALLATION**

AMBIENT TEMPERATURE

10 °C - 40 °C