



# TruBend Series 5000

Technical data

**TruBend 5085****TruBend 5130****TruBend 5170**

<b>PRESS FORCE</b>	850 kN	1300 kN	1700 kN
<b>BENDING LENGTH</b>	2210 mm	3230 mm	3230 mm
<b>BENDING LENGTH FOR ENLARGED VERSION (OPTION)</b>	2720 mm	-	4250 mm
<b>WIDTH BETWEEN COLUMNS</b>	1750 mm	2690 mm	2690 mm
<b>USABLE OPEN HEIGHT</b>	385 mm	385 mm	615 mm
<b>USABLE OPEN HEIGHT FOR ENLARGED VERSION (OPTION)</b>	615 mm	615 mm	-
<b>THROAT DEPTH</b>	420 mm	420 mm	420 mm
<b>USER INTERFACE</b>	Touchpoint TruBend	Touchpoint TruBend	Touchpoint TruBend
<b>MAX. WORKING SPEED</b>	25 mm/s	25 mm/s	25 mm/s
<b>RAPID SPEED</b>	220 mm/s	220 mm/s	220 mm/s
<b>DIMENSIONS</b>			
LENGTH	3020 mm	3980 mm	3980 mm
WIDTH	1800 mm	1800 mm	1900 mm
HEIGHT	2375 mm	2375 mm	3000 mm

**TruBend 5230****TruBend 5320**

<b>PRESS FORCE</b>	2300 kN	3200 kN
<b>BENDING LENGTH</b>	3230 mm	4420 mm
<b>BENDING LENGTH FOR ENLARGED VERSION (OPTION)</b>	4250 mm	-
<b>WIDTH BETWEEN COLUMNS</b>	2690 mm	3680 mm
<b>USABLE OPEN HEIGHT</b>	615 mm	615 mm
<b>USABLE OPEN HEIGHT FOR ENLARGED VERSION (OPTION)</b>	-	-
<b>THROAT DEPTH</b>	420 mm	420 mm
<b>USER INTERFACE</b>	Touchpoint TruBend	Touchpoint TruBend
<b>MAX. WORKING SPEED</b>	25 mm/s	25 mm/s
<b>RAPID SPEED</b>	220 mm/s	220 mm/s
<b>DIMENSIONS</b>		
LENGTH	4150 mm	5180 mm
WIDTH	2055 mm	2055 mm
HEIGHT	3200 mm	3200 mm