



# TruLaser Center 7030

Technical data



# TruLaser Center 7030

## INSTALLATION AREA

LENGTH	10135 mm
WIDTH (CART EXTENDED)	10720 mm
WIDTH (CART RETRACTED)	6420 mm
HEIGHT	3050 mm

**WEIGHT WITH ALL UNITS** 38860 kg

## NOMINAL WORKING RANGE

X AXIS	3000 mm
Y AXIS	1500 mm
Z AXIS	120 mm

## TRUDISK 6001 LASER-SPECIFIC DATA

MAXIMUM LASER POWER	6000 W
MINIMUM SHEET THICKNESS	1 mm
MAXIMUM SHEET THICKNESS, MILD STEEL	12.7 mm
MAXIMUM SHEET THICKNESS, STAINLESS STEEL	12.7 mm
MAXIMUM SHEET THICKNESS, ALUMINUM	6 mm
MAXIMUM SHEET THICKNESS, BRASS	6 mm
MAXIMUM SHEET THICKNESS, COPPER	6 mm

## SMARTGATE UNLOADING AUTOMATION

MAXIMUM PART SIZE	160 mm x 160 mm
MINIMUM PART SIZE	30 mm x 30 mm

## SORTMASTER SPEED UNLOADING AUTOMATION

MAXIMUM PART SIZE	2000 mm x 1500 mm
MINIMUM PART SIZE	90 mm x 60 mm