



# TruMark Station 5000

Technical data



# TruMark Station 5000

## WORKPIECE SPECIFICATION

|                                       |                          |
|---------------------------------------|--------------------------|
| MAX. WORKPIECE DIMENSIONS (W X H X D) | 680 mm x 500 mm x 700 mm |
| MAX. WORKPIECE WEIGHT                 | 50 kg                    |

## AVAILABLE MOTORIZED AXIS

|                             |                                 |
|-----------------------------|---------------------------------|
| TRAVERSE PATH OF THE Z AXIS | 500 mm 380 mm with TruMark 5010 |
| TRAVERSE PATH OF THE X AXIS | 300 mm                          |
| TRAVERSE PATH OF THE Y AXIS | 300 mm                          |
| TRAVELING SPEED Z           | 1.5 m/min                       |
| TRAVELING SPEED X           | 6 m/min                         |
| TRAVELING SPEED Y           | 6 m/min                         |

## CONNECTION AND CONSUMPTION

|                                   |               |
|-----------------------------------|---------------|
| ELECTRICAL CONNECTION (VOLTAGE)   | 115 V - 230 V |
| ELECTRICAL CONNECTION (FREQUENCY) | 50 Hz - 60 Hz |

## DIMENSIONS AND WEIGHT OF WORK STATION

|  |                            |
|--|----------------------------|
| DIMENSIONS OF WORK STATION (W X H X D) | 860 mm x 2000 mm x 1310 mm |
|--|----------------------------|

## LASER CLASS

|             |   |
|-------------|---|
| LASER CLASS | 1 |
|-------------|---|