



# TruPunch 1000 (S05)

Technical data



# TruPunch 1000 (S05)

Punching machines

## Technical data

	<b>TruPunch 1000 (S05) small format</b>	<b>TruPunch 1000 (S05) medium format</b>
<b>DIMENSIONS</b>		
WIDTH	6000 mm <sup>1</sup>	6550 mm <sup>1</sup>
DEPTH	7144 mm <sup>1</sup>	7144 mm <sup>1</sup>
HEIGHT	2155 mm <sup>1</sup>	2155 mm <sup>1</sup>
<b>MAX. STROKE RATE</b>		
PUNCHING (E = 1 MM)	600 RPM	600 RPM
MARKING	1300 RPM	1300 RPM
<b>WORKING RANGE</b>		
PUNCHING MODE, X AXIS	2050 mm	2500 mm
PUNCHING MODE, Y AXIS	1250 mm	1250 mm
MAX. SHEET THICKNESS	6.4 mm	6.4 mm
MAX. WORKPIECE WEIGHT	150 kg	150 kg
MAX. PUNCHING FORCE	165 kN	165 kN
<b>TOOLS</b>		
MULTITOOL TOOL CHANGING TIME	2.4 sec	2.4 sec
NUMBER OF TOOLS/CLAMPS	15 Pieces / 2 Pieces	18 Pieces / 2 Pieces
<b>PART REMOVAL</b>		
MAX. PART SIZE, PART REMOVAL FLAP, PUNCHES	180 mm x 150 mm	180 mm x 150 mm
MAX. PART SIZE - PUNCHING PART REMOVAL FLAP (WITH MOVING TABLE)	180 mm x 500 mm	180 mm x 500 mm
MAX. PART SIZE - FIXED PUNCHING CHUTE (WITH MOVING TABLE)	460 mm x 500 mm	460 mm x 500 mm
<b>CONSUMPTION VALUES</b>		

Subject to changes. The details in our offer and order confirmation are definitive.



# TruPunch 1000 (S05)

Punching machines

## Technical data

---

	<b>TruPunch 1000 (S05) small format</b>	<b>TruPunch 1000 (S05) medium format</b>
AVERAGE POWER CONSUMPTION OF ACTIVE AUTO-SHUTDOWN	0.3 kW	0.3 kW
AVERAGE POWER INPUT IN PRODUCTION	4.3 kW	4.3 kW

---

Subject to changes. The details in our offer and order confirmation are definitive.

## Footnotes

---

1 — The dimensions are approximate; the dimensions specified in the installation plan are valid.