



# TruTool TKF 700

Technical data

**TruTool TKF 700 30°  
bevel angle****TruTool TKF 700  
37.5° bevel angle****TruTool TKF 700 45°  
bevel angle****MAXIMUM CHAMFER LENGTHS**MAXIMUM CHAMFER LENGTH,  
STEEL 400 N/MM<sup>2</sup>

7 mm

7 mm

7 mm

MAXIMUM CHAMFER LENGTH,  
STEEL 600 N/MM<sup>2</sup>

5.7 mm

5.7 mm

5.7 mm

MAXIMUM CHAMFER LENGTH,  
STEEL 800 N/MM<sup>2</sup>

4 mm

4 mm

4 mm

**RADII**

SMALLEST RADIUS

40 mm

40 mm

40 mm

**GENERAL**

WORKING SPEED

1.5 m/min

1.5 m/min

1.5 m/min

STROKE RATE AT NOMINAL LOAD

815 1/min

815 1/min

815 1/min

NOMINAL INPUT POWER

1700 W

1700 W

1700 W

SHEET THICKNESS

1 mm - 20 mm

1 mm - 20 mm

1 mm - 20 mm

**WEIGHT**

WEIGHT WITHOUT CABLE

5.3 kg

5.3 kg

5.3 kg

---

Subject to changes. The information in our offer and our order confirmation is definitive.