



TruTool F 300 with 1700 W motor

Technical data



TruTool F 300 with 1400 W motor

MAXIMUM SHEET THICKNESSES

| | |
|--|---------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM ² (MINIMUM) | 0.75 mm |
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM ² (MAXIMUM) | 1.25 mm |

FLANGE HEIGHT (B)

| | |
|---|------------|
| FLANGE HEIGHT (B) WITH SHEET THICKNESS 0.75 - 1.0 | 9 - 11 mm |
| FLANGE HEIGHT (B) WITH SHEET THICKNESS > 1.0 - 1.25 | 11 - 13 mm |

RADII

| | |
|-----------------------------------|--------|
| SMALLEST INNER RADIUS (PREFORMED) | 150 mm |
| SMALLEST OUTER RADIUS | 300 mm |

GENERAL

| | |
|---------------------|------------------------|
| WORKING SPEED | 6.5 m/min - 10.5 m/min |
| NOMINAL INPUT POWER | 1700 W |

WEIGHT

| | |
|----------------------|--------|
| WEIGHT WITHOUT CABLE | 6.4 kg |
|----------------------|--------|