



# TruTool S 160

Technical data

## TruTool S 160

### MAXIMUM SHEET THICKNESSES

|   |        |
|---|--------|
| MAXIMUM SHEET THICKNESS, STEEL UP TO 400 N/MM <sup>2</sup>    | 1.6 mm |
| MAXIMUM SHEET THICKNESS, STEEL UP TO 600 N/MM <sup>2</sup>    | 1.2 mm |
| MAXIMUM SHEET THICKNESS, STEEL UP TO 800 N/MM <sup>2</sup>    | 1 mm   |
| MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM <sup>2</sup> | 2 mm   |

### RADII

|                 |       |
|-----------------|-------|
| SMALLEST RADIUS | 15 mm |
|-----------------|-------|

### GENERAL

|                               |                    |
|-------------------------------|--------------------|
| WORKING SPEED                 | 8 m/min - 12 m/min |
| STROKE RATE WITH NOMINAL LOAD | 4800 RPM           |
| STARTING HOLE DIAMETER        | 27 mm              |
| NOMINAL POWER CONSUMPTION     | 350 W              |

### WEIGHT

|                      |        |
|----------------------|--------|
| WEIGHT WITHOUT CABLE | 1.6 kg |
|----------------------|--------|