



# TruTool TKA 500

Technical data



**TruTool TKA 500  
without tool****TruTool TKA 500 45°  
tool****MAXIMUM CHAMFER LENGTHS**

MAXIMUM CHAMFER LENGTH, STEEL 400 N/MM <sup>2</sup>	5 mm	5 mm
MAXIMUM CHAMFER LENGTH, STEEL 600 N/MM <sup>2</sup>	2.5 mm	2.5 mm
MAXIMUM CHAMFER LENGTH, STEEL 800 N/MM <sup>2</sup>	1.5 mm	1.5 mm
MAXIMUM CHAMFER LENGTH, ALUMINUM 250 N/MM <sup>2</sup>	9 mm	9 mm

**RADII**

SMALLEST INNER RADIUS	12 mm	12 mm
-----------------------	-------	-------

**GENERAL**

MINIMUM SHEET THICKNESS WITH IMPELLER FOR THIN SHEETS	0.7 mm	0.7 mm
WORKING SPEED	3 m/min - 4 m/min	3 m/min - 4 m/min
NOMINAL INPUT POWER	1400 W	1400 W
REVOLUTION SPEED DURING IDLE RUN	8390 1/min	8390 1/min

**WEIGHT**

WEIGHT WITHOUT CABLE	3.5 kg	3.5 kg
----------------------	--------	--------