



TruTool TF 350 Li-ion rechargeable battery 18 V

Technical data



TruTool TF 350 Li-ion rechargeable battery 18 V

MAXIMUM SHEET THICKNESSES

| | |
|----------------------------------------------------------------|--------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM ² | 3.5 mm |
| MAXIMUM SHEET THICKNESS, STEEL 600 N/MM ² | 2.5 mm |
| MAXIMUM SHEET THICKNESS, ALUMINIUM UP TO 250 N/MM ² | 4 mm |

GENERAL

| | |
|---------------------------|--------|
| MINIMUM SHEET THICKNESS | 0.8 mm |
| MAXIMUM JOINING FORCE | 25 kN |
| MAXIMUM STROKE RATE | 2 1/s |
| MINIMUM EDGE SPACING | 8 mm |
| MAXIMUM EDGE SPACING | 58 mm |
| MAXIMUM FLANGE HEIGHT (B) | 36 mm |
| VOLTAGE | 18 V |

WEIGHT

| | |
|----------------------------------------|--------|
| WEIGHT (WITH 2 AH RECHARGABLE BATTERY) | 7.8 kg |
| WEIGHT (WITH 4 AH RECHARGABLE BATTERY) | 8.1 kg |