



TruDisk

Technical data

TruDisk 1000**TruDisk 2000****TruDisk 3001****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	1000 W	2000 W	3000 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	60 W - 1000 W with active power regulation	60 W - 2000 W with active power regulation	80 W - 3000 W with active power regulation
BEAM QUALITY AT THE INPUT COUPLING IN THE LLK	2 mm ■ mrad	2 mm ■ mrad	4 mm ■ mrad
NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK	0.1	0.1	0.1
WAVELENGTH	1030 nm	1030 nm	1030 nm
MINIMUM LASER LIGHT CABLE DIAMETER	50 µm	50 µm	100 µm

STRUCTURAL DESIGN

WIDTH	1175 mm	1175 mm	1175 mm
HEIGHT	1430 mm	1430 mm	1430 mm
DEPTH	725 mm	725 mm	725 mm
MAXIMUM NUMBER OF LASER LIGHT CABLES	2	2	2
MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE	4	4	4

INSTALLATION

PROTECTION CLASS	IP54	IP54	IP54
AMBIENT TEMPERATURE	10 °C - 50 °C	10 °C - 50 °C	10 °C - 50 °C

TruDisk 3002**TruDisk 3006****TruDisk 4000****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	3000 W	3000 W	4000 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	80 W - 3000 W with active power regulation	80 W - 3000 W with active power regulation	80 W - 4000 W with active power regulation
BEAM QUALITY AT THE INPUT COUPLING IN THE LLK	8 mm ■ mrad	25 mm ■ mrad	2 mm ■ mrad
NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK	0.1	0.1	0.1
WAVELENGTH	1030 nm	1030 nm	1030 nm
MINIMUM LASER LIGHT CABLE DIAMETER	200 µm	600 µm	50 µm

STRUCTURAL DESIGN

WIDTH	1175 mm	1175 mm	1175 mm
HEIGHT	1430 mm	1430 mm	1430 mm
DEPTH	725 mm	725 mm	725 mm
MAXIMUM NUMBER OF LASER LIGHT CABLES	2	2	2

TruDisk 3002**TruDisk 3006****TruDisk 4000**

MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE

4

4

4

INSTALLATION

PROTECTION CLASS

IP54

IP54

IP54

AMBIENT TEMPERATURE

10 °C - 50 °C

10 °C - 50 °C

10 °C - 50 °C

TruDisk 4001**TruDisk 4002****TruDisk 4006****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE

4000 W

4000 W

4000 W

TYPICAL POWER CONSTANCY AT RATED POWER

± 1 % with active power regulation

± 1 % with active power regulation

± 1 % with active power regulation

CONTINUOUSLY ADJUSTABLE POWER RANGE

80 W - 4000 W with active power regulation

80 W - 4000 W with active power regulation

80 W - 4000 W with active power regulation

BEAM QUALITY AT THE INPUT COUPLING IN THE LLK

4 mm ■ mrad

8 mm ■ mrad

25 mm ■ mrad

NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK

0.1

0.1

0.1

WAVELENGTH

1030 nm

1030 nm

1030 nm

MINIMUM LASER LIGHT CABLE DIAMETER

100 µm

200 µm

600 µm

STRUCTURAL DESIGN

WIDTH

1175 mm

1175 mm

1175 mm

HEIGHT

1430 mm

1430 mm

1430 mm

DEPTH

725 mm

725 mm

725 mm

MAXIMUM NUMBER OF LASER LIGHT CABLES

2

2

2

MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE

4

4

4

INSTALLATION

PROTECTION CLASS

IP54

IP54

IP54

AMBIENT TEMPERATURE

10 °C - 50 °C

10 °C - 50 °C

10 °C - 50 °C

TruDisk 5000**TruDisk 5001****TruDisk 5002****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE

5000 W

5000 W

5000 W

TYPICAL POWER CONSTANCY AT RATED POWER

± 1 % with active power regulation

± 1 % with active power regulation

± 1 % with active power regulation

CONTINUOUSLY ADJUSTABLE POWER RANGE

100 W - 5000 W with active power regulation

120 W - 5000 W with active power regulation

120 W - 5000 W with active power regulation

BEAM QUALITY AT THE INPUT COUPLING IN THE LLK

2 mm ■ mrad

4 mm ■ mrad

8 mm ■ mrad

NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK

0.1

0.1

0.1

TruDisk 5000**TruDisk 5001****TruDisk 5002**

WAVELENGTH	1030 nm	1030 nm	1030 nm
MINIMUM LASER LIGHT CABLE DIAMETER	50 µm	100 µm	200 µm

STRUCTURAL DESIGN

WIDTH	1175 mm	1175 mm	1175 mm
HEIGHT	1430 mm	1430 mm	1430 mm
DEPTH	725 mm	725 mm	725 mm
MAXIMUM NUMBER OF LASER LIGHT CABLES	2	2	2
MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE	4	4	4

INSTALLATION

PROTECTION CLASS	IP54	IP54	IP54
AMBIENT TEMPERATURE	10 °C - 50 °C	10 °C - 50 °C	10 °C - 50 °C

TruDisk 5006**TruDisk 6001****TruDisk 6002****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	5000 W	6000 W	6000 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	120 W - 5000 W with active power regulation	120 W - 6000 W with active power regulation	120 W - 6000 W with active power regulation
BEAM QUALITY AT THE INPUT COUPLING IN THE LLK	25 mm ■ mrad	4 mm ■ mrad	8 mm ■ mrad
NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK	0.1	0.1	0.1
WAVELENGTH	1030 nm	1030 nm	1030 nm
MINIMUM LASER LIGHT CABLE DIAMETER	600 µm	100 µm	200 µm

STRUCTURAL DESIGN

WIDTH	1175 mm	1175 mm	1175 mm
HEIGHT	1430 mm	1430 mm	1430 mm
DEPTH	725 mm	725 mm	725 mm
MAXIMUM NUMBER OF LASER LIGHT CABLES	2	2	2
MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE	4	4	4

INSTALLATION

PROTECTION CLASS	IP54	IP54	IP54
AMBIENT TEMPERATURE	10 °C - 50 °C	10 °C - 50 °C	10 °C - 50 °C

TruDisk 6006**TruDisk 8001****TruDisk 10001**

TruDisk 6006**TruDisk 8001****TruDisk 10001****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	6000 W	8000 W	10000 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	120 W - 6000 W with active power regulation	160 W with active power regulation	240 W - 10000 W with active power regulation
BEAM QUALITY AT THE INPUT COUPLING IN THE LLK	25 mm ■ mrad	4 mm ■ mrad	4 mm ■ mrad
NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK	0.1	0.1	0.1
WAVELENGTH	1030 nm	1030 nm	1030 nm
MINIMUM LASER LIGHT CABLE DIAMETER	600 µm	100 µm	100 µm

STRUCTURAL DESIGN

WIDTH	1175 mm	1175 mm	1990 mm
HEIGHT	1430 mm	1430 mm	1550 mm
DEPTH	725 mm	725 mm	1200 mm
MAXIMUM NUMBER OF LASER LIGHT CABLES	2	2	4
MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE	4	4	6

INSTALLATION

PROTECTION CLASS	IP54	IP54	IP54
AMBIENT TEMPERATURE	10 °C - 50 °C	10 °C - 50 °C	10 °C - 50 °C

TruDisk 10002**TruDisk 10003****TruDisk 12001****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	10000 W	10000 W	12000 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	200 W - 10000 W with active power regulation	200 W - 10000 W with active power regulation	240 W - 12000 W with active power regulation
BEAM QUALITY AT THE INPUT COUPLING IN THE LLK	8 mm ■ mrad	12 mm ■ mrad	4 mm ■ mrad
NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK	0.1	0.1	0.1
WAVELENGTH	1030 nm	1030 nm	1030 nm
MINIMUM LASER LIGHT CABLE DIAMETER	200 µm	300 µm	100 µm

STRUCTURAL DESIGN

WIDTH	1990 mm	1990 mm	1990 mm
HEIGHT	1550 mm	1550 mm	1550 mm
DEPTH	1200 mm	1200 mm	1200 mm
MAXIMUM NUMBER OF LASER LIGHT CABLES	4	4	4

TruDisk 10002**TruDisk 10003****TruDisk 12001**

MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE

6

6

6

INSTALLATION

PROTECTION CLASS

IP54

IP54

IP54

AMBIENT TEMPERATURE

10 °C - 50 °C

10 °C - 50 °C

10 °C - 50 °C

TruDisk 12002**TruDisk 12003****TruDisk 16002****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE

12000 W

12000 W

16000 W

TYPICAL POWER CONSTANCY AT RATED POWER

± 1 % with active power regulation

± 1 % with active power regulation

± 1 % with active power regulation

CONTINUOUSLY ADJUSTABLE POWER RANGE

240 W - 12000 W with active power regulation

240 W - 12000 W with active power regulation

320 W - 16000 W

BEAM QUALITY AT THE INPUT COUPLING IN THE LLK

8 mm ■ mrad

12 mm ■ mrad

8 mm ■ mrad

NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK

0.1

0.1

0.1

WAVELENGTH

1030 nm

1030 nm

1030 nm

MINIMUM LASER LIGHT CABLE DIAMETER

200 µm

300 µm

200 µm

STRUCTURAL DESIGN

WIDTH

1990 mm

1990 mm

2800 mm

HEIGHT

1550 mm

1550 mm

1550 mm

DEPTH

1200 mm

1200 mm

1400 mm

MAXIMUM NUMBER OF LASER LIGHT CABLES

4

4

6

MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED DEVICE SIZE

6

6

-

INSTALLATION

PROTECTION CLASS

IP54

IP54

IP54

AMBIENT TEMPERATURE

10 °C - 50 °C

10 °C - 50 °C

10 °C - 50 °C

TruDisk 16003**LASER PARAMETERS**

LASER POWER ON THE WORKPIECE

16000 W

TYPICAL POWER CONSTANCY AT RATED POWER

± 1 % with active power regulation

CONTINUOUSLY ADJUSTABLE POWER RANGE

320 W - 16000 W

BEAM QUALITY AT THE INPUT COUPLING IN THE LLK

12 mm ■ mrad

NUMERICAL APERTURE ON THE OUTPUT COUPLING AFTER LLK

0.1

WAVELENGTH

1030 nm

MINIMUM LASER LIGHT CABLE DIAMETER

300 µm

TruDisk 16003

STRUCTURAL DESIGN

WIDTH 2800 mm

HEIGHT 1550 mm

DEPTH 1400 mm

MAXIMUM NUMBER OF LASER LIGHT CABLES 6

MAXIMUM NUMBER OF LASER LIGHT CABLES FOR EXTENDED
DEVICE SIZE -

INSTALLATION

PROTECTION CLASS IP54

AMBIENT TEMPERATURE 10 °C - 50 °C