



TruLaser Tube 3000 fiber

Technical data

TruLaser Tube 3000 fiber

ROUND TUBE

MAXIMUM OUTSIDE DIAMETER	152 mm
MAXIMUM OUTSIDE DIAMETER (OPTIONAL)	170 mm ¹

RECTANGULAR PROFILE

MAXIMUM SIDE LENGTH AND OUTER CIRCLE DIAMETER	152 mm / 170 mm
---	-----------------

MAXIMUM RAW MATERIAL LENGTH FOR AUTOMATIC LOADING

FOR LOADMASTER TUBE 6.5 M	6500 mm
FOR LOADMASTER TUBE 8.0 M	8000 mm ²

FINISHED PART LENGTH

FOR UNLOADING UNIT 3 M	3000 mm
FOR UNLOADING UNIT 3 M + 1.5 M	4500 mm ²

WORKPIECE WEIGHT

MAXIMUM PATH WEIGHT (STANDARD/OPTIONAL)	18.5 kg/m / - kg/m
---	--------------------

MAXIMUM RAW MATERIAL WEIGHT WITH AUTOMATIC LOADING

WITH LOADMASTER TUBE 6.5 M	120 kg
WITH LOADMASTER TUBE 8.0 M	148 kg

Footnotes

1 — Round tubes with a diameter of 152 mm to 170 mm can only be manually loaded.

2 — Value for extended versions (option)