



# TruTool F 301 Li-ion rechargeable battery 18 V

Technical data



**MAXIMUM SHEET THICKNESSES**

|  |         |
|--|---------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM <sup>2</sup> (MINIMUM) | 0.45 mm |
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM <sup>2</sup> (MAXIMUM) | 1 mm    |

**FLANGE HEIGHT (B)**

|   |         |
|---|---------|
| FLANGE HEIGHT (B) WITH SHEET THICKNESS 0.45 - 1.0 | 8-11 mm |
|---|---------|

**RADII**

|                                   |        |
|-----------------------------------|--------|
| SMALLEST INNER RADIUS (PREFORMED) | 150 mm |
| SMALLEST OUTER RADIUS             | 300 mm |

**GENERAL**

|                        |         |
|------------------------|---------|
| MAXIMUM FOLD THICKNESS | 1 mm    |
| WORKING SPEED          | 4 m/min |

**WEIGHT**

|   |        |
|---|--------|
| WEIGHT (WITH 2 AH RECHARGEABLE BATTERY) | 5.6 kg |
| WEIGHT (WITH 4 AH RECHARGEABLE BATTERY) | 5.9 kg |