



TruMicro Series 7000

Technical data

TruMicro 7050**TruMicro 7060 (new generation)****TruMicro 7060****LASER PARAMETERS**

AVERAGE OUTPUT POWER	750 W	1000 W	850 W
BEAM QUALITY	20 mm ■ mrad	10 mm ■ mrad , depends on the optical laser cable that is used	20 mm ■ mrad
WAVELENGTH	1030 nm	1030 nm	1030 nm
PULSE DURATION	30 ns	30 ns	30 ns
MAXIMUM PULSE ENERGY	80 mJ	100 mJ	80 mJ
MINIMUM REPETITION RATE	5 kHz	5 kHz	5 kHz
MAXIMUM REPETITION RATE	100 kHz	100 kHz	100 kHz
MINIMUM LASER LIGHT CABLE DIAMETER	400 µm	-	400 µm

STRUCTURAL DESIGN

DIMENSIONS OF SUPPLY UNIT (W X H X D)	1460 mm x 1350 mm x 730 mm	1340 mm x 1430 mm x 725 mm	1460 mm x 1350 mm x 730 mm
---------------------------------------	----------------------------	----------------------------	----------------------------

INSTALLATION

PROTECTION CLASS	IP54	IP54	IP54
------------------	------	------	------

TruMicro 7070 (new generation)**LASER PARAMETERS**

AVERAGE OUTPUT POWER	2000 W
BEAM QUALITY	10 mm ■ mrad , depends on the optical laser cable that is used
WAVELENGTH	1030 nm
PULSE DURATION	30 ns
MAXIMUM PULSE ENERGY	100 mJ
MINIMUM REPETITION RATE	5 kHz
MAXIMUM REPETITION RATE	250 kHz
MINIMUM LASER LIGHT CABLE DIAMETER	300 µm

STRUCTURAL DESIGN

DIMENSIONS OF SUPPLY UNIT (W X H X D)	1340 mm x 1430 mm x 725 mm
---------------------------------------	----------------------------

INSTALLATION

PROTECTION CLASS	IP54
------------------	------

Subject to changes. The information in our offer and our order confirmation is definitive.