



TruPrint 2000

Technical data

TruPrint 2000

BUILD VOLUME (CYLINDER) Diameter 200 mm x 200 mm Height

EFFECTIVE BUILD VOLUME (STANDARD) Diameter 200 mm x 200 mm Height

PROCESSABLE RAW MATERIALS

Metal powders for welding, such as stainless steels, tool steels and aluminium, nickel-base, cobalt-chrome or titanium metal alloys, amorphous metals. Current availability of materials and their parameters available on request.

PREHEATING (STANDARD) Down to 200 °C

MAXIMUM LASER POWER AT THE WORKPIECE (TRUMPF FIBRE LASER) 300 W

BEAM DIAMETER (STANDARD) 55 µm

LAYER THICKNESS 20 - 100 µm

CONNECTION AND CONSUMPTION

ELECTRICAL CONNECTION (VOLTAGE) 400/460 V

ELECTRICAL CONNECTION (CURRENT INTENSITY) 32 A

ELECTRICAL CONNECTION (LINE FREQUENCY) 50 Hz / 60 Hz

SHIELDING GAS Nitrogen, argon

STRUCTURAL DESIGN

DIMENSIONS (W X H X D) 2180 mm x 2030 mm x 1400 mm

WEIGHT (INCLUDING POWDER) 3200 kg

Subject to changes. The information in our offer and our order confirmation is definitive.