



TruLaser 2030 fiber

Technical data

TruLaser 2030 fiber

DIMENSIONS

LENGTH	8276 mm
WIDTH	6764 mm
HEIGHT	2300 mm

WEIGHT

WEIGHT, BASIC MACHINE	7750 kg
-----------------------	---------

MAX. SPEED

SIMULTANEOUS	140 m/min
--------------	-----------

WORKING RANGE

X AXIS	3000 mm
Y AXIS	1500 mm
MAX. WORKPIECE WEIGHT	900 kg

LASER-SPECIFIC DATA - TRUDISK 2001

MAX. LASER OUTPUT	2000 W
MAX. SHEET THICKNESS, MILD STEEL	16 mm
MAX. SHEET THICKNESS, STAINLESS STEEL	8 mm
MAX. SHEET THICKNESS, COPPER	3 mm
MAX. SHEET THICKNESS, BRASS	3 mm
MAX. SHEET THICKNESS, ALUMINUM	6 mm

LASER-SPECIFIC DATA - TRUDISK 3001

MAX. LASER OUTPUT	3000 W
MAX. SHEET THICKNESS, MILD STEEL	20 mm
MAX. SHEET THICKNESS, STAINLESS STEEL	16 mm
MAX. SHEET THICKNESS, ALUMINUM	12 mm
MAX. SHEET THICKNESS, COPPER	6 mm
MAX. SHEET THICKNESS, BRASS	6 mm

LASER-SPECIFIC DATA - TRUDISK 4001

MAX. LASER OUTPUT	4000 W
MAX. SHEET THICKNESS, MILD STEEL	25 mm
MAX. SHEET THICKNESS, STAINLESS STEEL	20 mm
MAX. SHEET THICKNESS, ALUMINUM	20 mm
MAX. SHEET THICKNESS, COPPER	8 mm
MAX. SHEET THICKNESS, BRASS	8 mm

CONSUMPTION VALUES

AVERAGE POWER INPUT IN PRODUCTION - TRUDISK 2001	11 kW
AVERAGE POWER INPUT IN PRODUCTION - TRUDISK 3001	13 kW
AVERAGE POWER INPUT IN PRODUCTION - TRUDISK 4001	13 kW

Subject to changes. The information in our offer and our order confirmation is definitive.