



# TruTool TKA 1500

Technical data



**TruTool TKA 1500  
without tool****TruTool TKA 1500 45°  
tool****MAXIMUM CHAMFER LENGTHS**

MAXIMUM CHAMFER LENGTH, STEEL 400 N/MM <sup>2</sup>	15 mm	15 mm
MAXIMUM CHAMFER LENGTH, STEEL 600 N/MM <sup>2</sup>	12 mm	12 mm
MAXIMUM CHAMFER LENGTH, STEEL 800 N/MM <sup>2</sup>	10 mm	10 mm
MAXIMUM CHAMFER LENGTH, ALUMINUM 250 N/MM <sup>2</sup>	15 mm	15 mm

**MAXIMUM CHAMFER HEIGHTS**

MAXIMUM CHAMFER HEIGHT, STEEL 400 N/MM <sup>2</sup>	10.6 mm	10.6 mm
MAXIMUM CHAMFER HEIGHT, STEEL 600 N/MM <sup>2</sup>	8.5 mm	8.5 mm
MAXIMUM CHAMFER HEIGHT, STEEL 800 N/MM <sup>2</sup>	7.1 mm	7.1 mm
MAXIMUM CHAMFER HEIGHT, ALUMINUM 250 N/MM <sup>2</sup>	10.6 mm	10.6 mm

**RADII**

SMALLEST INNER RADIUS	30 mm	30 mm
SMALLEST BORE HOLE (∅)	55 mm	55 mm

**GENERAL**

MINIMUM SHEET THICKNESS	3 + hs mm	3 + hs mm
WORKING SPEED	1 m/min - 1.5 m/min	1 m/min - 1.5 m/min
NOMINAL INPUT POWER	2600 W	2600 W
REVOLUTION SPEED DURING IDLE RUN	6700 1/min	6700 1/min

**WEIGHT**

WEIGHT WITHOUT CABLE	10 kg	10 kg
----------------------	-------	-------