



# TruLaser 5030 / 5040 / 5060

Technical data

**TruLaser 5030****TruLaser 5040****TruLaser 5060****DIMENSIONS**

LENGTH	9950 mm	12510 mm	16930 mm
WIDTH	4600 mm	5400 mm	5420 mm
HEIGHT	2400 mm	2400 mm	2500 mm

**MAXIMUM SPEED**

SIMULTANEOUS	300 m/min	300 m/min	300 m/min
--------------	-----------	-----------	-----------

**WORKING RANGE**

X AXIS	3000 mm	4000 mm	6000 mm
Y AXIS	1500 mm	2000 mm	2000 mm
MAXIMUM WORKPIECE WEIGHT	1800 kg	3200 kg	4800 kg

**LASER-SPECIFIC DATA -  
TRUFLOW 6000**

MAXIMUM LASER POWER	6000 W	6000 W	6000 W
MAXIMUM SHEET THICKNESS, MILD STEEL	25 mm	25 mm	25 mm
MAXIMUM SHEET THICKNESS, STAINLESS STEEL	25 mm	25 mm	25 mm
MAXIMUM SHEET THICKNESS, ALUMINUM	16 mm	16 mm	16 mm

**CONSUMPTION VALUES**

AVERAGE POWER INPUT IN PRODUCTION - TRUFLOW 6000	32 kW	32 kW	32 kW
AVERAGE POWER INPUT IN PRODUCTION - TRUFLOW 8000	40 kW	40 kW	40 kW

Subject to changes. The information in our offer and our order confirmation is definitive.