



# TruMark Station 7000

Technical data

## TruMark Station 7000

## TruMark Station 7000R

### WORKPIECE SPECIFICATION

MAXIMUM WORKPIECE DIMENSIONS WITHOUT Y AXIS (W X H X D)	1000 mm x 450* mm x 650 mm * Abhängig von Laser und Optik	-
MAXIMUM WORKPIECE DIMENSIONS WITH Y AXIS (W X H X D)	960 mm x 450 mm x 375 mm * Abhängig von Laser und Optik	-
MAXIMUM WORKPIECE WEIGHT	-	35 kg per page
MAXIMUM WORKPIECE WEIGHT (WITHOUT Y AXIS)	100 kg	-
MAXIMUM WORKPIECE WEIGHT (WITH Y AXIS)	50 kg	-
DIAMETER OF ROTARY PLATE		770 mm

### AVAILABLE MOTORIZED AXIS

TRAVERSE PATH OF THE Z AXIS	500 mm	500 mm
TRAVERSE PATH OF THE X AXIS	650 mm	650 mm
TRAVERSE PATH OF THE Y AXIS	350 mm (not available for rotary table)	-
Z TRAVERSE SPEED	6 m/min	6 m/min
X TRAVERSE SPEED	6 m/min	6 m/min
Y TRAVERSE SPEED	6 m/min	-

### DIMENSIONS AND WEIGHT OF WORK STATION

DIMENSIONS OF WORK STATION (W X H X D)	1150 mm x 2000 mm x 1410* mm * bei Rotationswechslervariante 1620 mm	1150 mm x 2010 mm x 1580 mm
--	--	-----------------------------

Subject to changes. The details in our offer and order confirmation are definitive.