

TRUMPF



TruTool C 160 chip clipper,  
12V LiHD rechargeable battery

Technical data

**TRUMPF**



## TruTool C 160 with chip clipper Li-ion 10.8 V

### MAXIMUM SHEET THICKNESSES

|   |             |
|---|-------------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM <sup>2</sup>          | 1.6 mm      |
| MAXIMUM SHEET THICKNESS, STEEL 600 N/MM <sup>2</sup>          | 1.2 mm      |
| MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM <sup>2</sup> | 2 mm        |
| SPIRAL DUCT, STEEL 400 N/MM <sup>2</sup>                      | 4 x 0,75 mm |

### RADII

|                 |       |
|-----------------|-------|
| SMALLEST RADIUS | 40 mm |
|-----------------|-------|

### GENERAL

|                             |                   |
|-----------------------------|-------------------|
| WORKING SPEED               | 5 m/min - 9 m/min |
| STROKE RATE AT NOMINAL LOAD | 3520 1/min        |
| STROKE RATE DURING IDLE RUN | 5500 1/min        |
| STARTING HOLE DIAMETER      | 15 mm             |
| VOLTAGE                     | 12 V              |

### WEIGHT

|   |        |
|---|--------|
| WEIGHT (WITH 4 AH RECHARGEABLE BATTERY) | 1.6 kg |
|---|--------|