



# TruHeat MF Series 3000 / 5000 / 7000

Technical data



**TruHeat MF 3010****TruHeat MF 3020****TruHeat MF 3030****OUTPUT**

RATED POWER	10 kW	20 kW	30 kW
MAXIMUM OUTPUT VOLTAGE	600 V eff	600 V eff	600 V eff
NOMINAL OPERATING FREQUENCY	5 kHz - 200 kHz	5 kHz - 200 kHz	5 kHz - 200 kHz
LENGTH OF POWER CABLE	5 m - 25 m	5 m - 25 m	5 m - 25 m

**NETWORK CONNECTION DATA**

LINE VOLTAGE	(±10%) 400 V - 480 V	(±10%) 400 V - 480 V	(±10%) 400 V - 480 V
LINE FREQUENCY	50 Hz - 60 Hz	50 Hz - 60 Hz	50 Hz - 60 Hz
LINE INPUT POWER	23 kVA	25 kVA	37 kVA
POWER FACTOR	0.96	0.96	0.96

**COMMUNICATION INTERFACES**

ANALOG/DIGITAL	yes	yes	- yes
RS 232 / RS 485	yes	yes	- yes
PROFIBUS	yes	yes	- yes

**HOUSING**

WEIGHT	87 kg	87 kg	87 kg
IP PROTECTION CLASS	IP21	IP21	IP21

**COOLING REQUIREMENTS**

MAXIMUM WATER PRESSURE	6 bar	6 bar	6 bar
MINIMUM PRESSURE DIFFERENCE	3 bar	3 bar	3 bar
MINIMUM FLOW RATE	16.5 l/min	16.5 l/min	16.5 l/min
COOLANT TEMPERATURE	- 35 °C	- 35 °C	- 35 °C

**OUTER CIRCLE**

WEIGHT	21 kg	21 kg	21 kg
IP PROTECTION CLASS	IP54	IP54	IP54

**GENERAL**

OVERALL EFFICIENCY	87 %	87 %	87 %
CERTIFICATES / STANDARDS	CE declaration of conformity	CE declaration of conformity	CE declaration of conformity

**AMBIENT CONDITIONS**

OUTSIDE TEMPERATURE	10 °C - 45 °C	10 °C - 45 °C	10 °C - 45 °C
---------------------	---------------	---------------	---------------

**TruHeat MF 3040****TruHeat MF 5010****TruHeat MF 5020****OUTPUT**

RATED POWER	40 kW	10 kW	20 kW
MAXIMUM OUTPUT VOLTAGE	600 V eff	600 V eff	600 V eff
NOMINAL OPERATING FREQUENCY	5 kHz - 200 kHz	5 kHz - 200 kHz	5 kHz - 200 kHz
LENGTH OF POWER CABLE	5 m - 25 m	5 m - 25 m	5 m - 25 m

**TruHeat MF 3040****TruHeat MF 5010****TruHeat MF 5020****NETWORK CONNECTION DATA**

LINE VOLTAGE	(±10%) 400 V - 480 V	(±10%) 400 V - 480 V	(±10%) 400 V - 480 V
LINE FREQUENCY	50 Hz - 60 Hz	50 Hz - 60 Hz	50 Hz - 60 Hz
LINE INPUT POWER	49 kVA	-	25 kVA
POWER FACTOR	0.96	0.96	0.96

**COMMUNICATION INTERFACES**

ANALOG/DIGITAL	yes	yes	- yes
RS 232 / RS 485	yes	yes	yes
PROFIBUS	yes	yes	- yes

**HOUSING**

WEIGHT	87 kg	105 kg	105 kg
IP PROTECTION CLASS	IP21	IP21	IP21

**COOLING REQUIREMENTS**

MAXIMUM WATER PRESSURE	6 bar	6 bar	6 bar
MINIMUM PRESSURE DIFFERENCE	3 bar	3 bar	3 bar
MINIMUM FLOW RATE	16.5 l/min	16.5 l/min	16.5 l/min
COOLANT TEMPERATURE	- 35 °C	- 35 °C	- 35 °C

**OUTER CIRCLE**

WEIGHT	21 kg	21 kg	21 kg
IP PROTECTION CLASS	IP54	IP54	IP54

**GENERAL**

OVERALL EFFICIENCY	87 %	87 %	87 %
CERTIFICATES / STANDARDS	CE declaration of conformity	CE declaration of conformity	CE declaration of conformity

**AMBIENT CONDITIONS**

OUTSIDE TEMPERATURE	10 °C - 45 °C	10 °C - 45 °C	10 °C - 45 °C
---------------------	---------------	---------------	---------------

**TruHeat MF 5030****TruHeat MF 7020****TruHeat MF 7030****OUTPUT**

RATED POWER	30 kW	20 kW	30 kW
MAXIMUM OUTPUT VOLTAGE	600 V eff	600 V eff	600 V eff
NOMINAL OPERATING FREQUENCY	5 kHz - 200 kHz	5 kHz - 200 kHz	5 kHz - 200 kHz
LENGTH OF POWER CABLE	5 m - 25 m	5 m - 25 m	5 m - 25 m

**NETWORK CONNECTION DATA**

LINE VOLTAGE	(±10%) 400 V - 480 V	(±10%) 400 V - 480 V	(±10%) 400 V - 480 V
LINE FREQUENCY	50 Hz - 60 Hz	50 Hz - 60 Hz	50 Hz - 60 Hz
LINE INPUT POWER	37 kVA	25 kVA	37 kVA
POWER FACTOR	0.96	0.96	0.96

**TruHeat MF 5030****TruHeat MF 7020****TruHeat MF 7030****COMMUNICATION INTERFACES**

ANALOG/DIGITAL	yes	yes	- yes
RS 232 / RS 485	- yes	- yes	yes
PROFIBUS	yes	yes	- yes

**HOUSING**

WEIGHT	105 kg	220 kg	220 kg
IP PROTECTION CLASS	IP21	IP54	IP54

**COOLING REQUIREMENTS**

MAXIMUM WATER PRESSURE	6 bar	6 bar	6 bar
MINIMUM PRESSURE DIFFERENCE	3 bar	3 bar	3 bar
MINIMUM FLOW RATE	16.5 l/min	21.5 l/min	21.5 l/min
COOLANT TEMPERATURE	- 35 °C	- 35 °C	- 35 °C

**OUTER CIRCLE**

WEIGHT	21 kg	21 kg	21 kg
IP PROTECTION CLASS	IP54	IP54	IP54

**GENERAL**

OVERALL EFFICIENCY	87 %	87 %	87 %
CERTIFICATES / STANDARDS	CE declaration of conformity	CE declaration of conformity	CE declaration of conformity

**AMBIENT CONDITIONS**

OUTSIDE TEMPERATURE	10 °C - 45 °C	10 °C - 45 °C	10 °C - 45 °C
---------------------	---------------	---------------	---------------

**TruHeat MF 7040****OUTPUT**

RATED POWER	40 kW
MAXIMUM OUTPUT VOLTAGE	600 V eff
NOMINAL OPERATING FREQUENCY	5 kHz - 200 kHz
LENGTH OF POWER CABLE	5 m - 25 m

**NETWORK CONNECTION DATA**

LINE VOLTAGE	(±10%) 400 V - 480 V
LINE FREQUENCY	50 Hz - 60 Hz
LINE INPUT POWER	49 kVA
POWER FACTOR	0.96

**COMMUNICATION INTERFACES**

ANALOG/DIGITAL	yes
RS 232 / RS 485	- yes
PROFIBUS	yes

# TruHeat MF 7040

## HOUSING

WEIGHT	220 kg
IP PROTECTION CLASS	IP54

## COOLING REQUIREMENTS

MAXIMUM WATER PRESSURE	6 bar
MINIMUM PRESSURE DIFFERENCE	3 bar
MINIMUM FLOW RATE	21.5 l/min
COOLANT TEMPERATURE	- 35 °C

## OUTER CIRCLE

WEIGHT	21 kg
IP PROTECTION CLASS	IP54

## GENERAL

OVERALL EFFICIENCY	87 %
CERTIFICATES / STANDARDS	CE declaration of conformity

## AMBIENT CONDITIONS

OUTSIDE TEMPERATURE	10 °C - 45 °C
---------------------	---------------