



TruPulse nano

Technical data

**TruPulse 1002 nano
(FK10-EP)****TruPulse 1002 nano
(FK10-HS)****TruPulse 1003 nano
(FK10-HS)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	20 W	20 W	30 W
MAXIMUM PEAK PULSE POWER	> 7 kW	> 7 kW	> 7 kW
BEAM QUALITY (M ²)	< 1.3	< 1.3	< 1.3
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1059 nm - 1065 nm	1059 nm - 1065 nm
MAXIMUM PULSE ENERGY	> 0.8 mJ	> 0.6 mJ	> 0.6 mJ
PULSE DURATION RANGE	3 ns - 2000 ns	10 ns - 240 ns	10 ns - 240 ns
PULSE REPETITION FREQUENCY	1 kHz - 4000 kHz	1 kHz - 1000 kHz	1 kHz - 1000 kHz

STRUCTURAL DESIGN

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

INSTALLATION

AMBIENT TEMPERATURE	0 °C - 45 °C	0 °C - 45 °C	0 °C - 45 °C
---------------------	--------------	--------------	--------------

**TruPulse 1005 nano
(FK10-HS)****TruPulse 1010 nano
(FK10-EP)****TruPulse 2002 nano
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	50 W	100 W	20 W
MAXIMUM PEAK PULSE POWER	> 7 kW	> 7 kW	> 10 kW
BEAM QUALITY (M ²)	< 1.3	< 1.3	< 1.6
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1059 nm - 1065 nm	1059 nm - 1065 nm
MAXIMUM PULSE ENERGY	> 0.6 mJ	> 1 mJ	> 1.2 mJ
PULSE DURATION RANGE	11 ns - 220 ns	4 ns - 2000 ns	3 ns - 2000 ns
PULSE REPETITION FREQUENCY	1 kHz - 1000 kHz	1 kHz - 4000 kHz	1 kHz - 4000 kHz

STRUCTURAL DESIGN

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	377 mm x 249 mm x 115 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	--------------------------	-------------------------

INSTALLATION

AMBIENT TEMPERATURE	0 °C - 42 °C	5 °C - 40 °C	0 °C - 45 °C
---------------------	--------------	--------------	--------------

**TruPulse 2002 nano
(FK10-RM)****TruPulse 2003 nano
(FK10-RM)****TruPulse 2005 nano
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	20 W	30 W	50 W
MAXIMUM PEAK PULSE POWER	> 10 kW	> 10 kW	> 10 kW
BEAM QUALITY (M ²)	< 1.6	< 1.6	< 1.6
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1059 nm - 1065 nm	1059 nm - 1065 nm
MAXIMUM PULSE ENERGY	> 1 mJ	> 1 mJ	> 1.2 mJ
PULSE DURATION RANGE	26 ns - 250 ns	26 ns - 250 ns	3 ns - 2000 ns
PULSE REPETITION FREQUENCY	1 kHz - 500 kHz	1 kHz - 500 kHz	1 kHz - 4000 kHz

**TruPulse 2002 nano
(FK10-RM)****TruPulse 2003 nano
(FK10-RM)****TruPulse 2005 nano
(FK10-EP)****STRUCTURAL DESIGN**

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

INSTALLATION

AMBIENT TEMPERATURE	0 °C - 45 °C	0 °C - 45 °C	0 °C - 40 °C
---------------------	--------------	--------------	--------------

**TruPulse 2005 nano
(FK10-RM)****TruPulse 2007 nano
(FK10-EP)****TruPulse 2007 nano
(FK10-RM)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	50 W	70 W	70 W
MAXIMUM PEAK PULSE POWER	> 10 kW	> 10 kW	> 10 kW
BEAM QUALITY (M ²)	< 1.6	< 1.6	< 1.6
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1059 nm - 1065 nm	1059 nm - 1065 nm
MAXIMUM PULSE ENERGY	> 1 mJ	> 1.2 mJ	> 1 mJ
PULSE DURATION RANGE	26 ns - 250 ns	3 ns - 2000 ns	28 ns - 260 ns
PULSE REPETITION FREQUENCY	1 kHz - 500 kHz	1 kHz - 4000 kHz	1 kHz - 500 kHz

STRUCTURAL DESIGN

DIMENSIONS (W X H X D)	347 mm x 201 mm x 95 mm	377 mm x 249 mm x 95 mm	377 mm x 249 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

INSTALLATION

AMBIENT TEMPERATURE	0 °C - 40 °C	0 °C - 40 °C	0 °C - 40 °C
---------------------	--------------	--------------	--------------

**TruPulse 2010 nano
(FK10-EP)****TruPulse 2013 nano
(FK10-EP)****TruPulse 2020 nano
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	100 W	130 W	200 W
MAXIMUM PEAK PULSE POWER	> 10 kW	> 10 kW	> 10 kW
BEAM QUALITY (M ²)	< 1.6	< 1.6	< 1.6
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1059 nm - 1065 nm	1059 nm - 1065 nm
MAXIMUM PULSE ENERGY	> 1.3 mJ	> 1.5 mJ	> 1.5 mJ
PULSE DURATION RANGE	4 ns - 2000 ns	3 ns - 2000 ns	9 ns - 2000 ns
PULSE REPETITION FREQUENCY	1 kHz - 4000 kHz	1 kHz - 4000 kHz	1 kHz - 4000 kHz

STRUCTURAL DESIGN

DIMENSIONS (W X H X D)	377 mm x 249 mm x 115 mm	423 mm x 417 mm x 133 mm	423 mm x 417 mm x 133 mm
------------------------	--------------------------	--------------------------	--------------------------

INSTALLATION

AMBIENT TEMPERATURE	0 °C - 40 °C	10 °C - 45 °C	10 °C - 40 °C
---------------------	--------------	---------------	---------------

**TruPulse 2030 nano
(FK10-EP)****TruPulse 3002 nano
(FK10-EP)****TruPulse 3002 nano
(FK10-HS)**

**TruPulse 2030 nano
(FK10-EP)****TruPulse 3002 nano
(FK10-EP)****TruPulse 3002 nano
(FK10-HS)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	300 W	20 W	20 W
MAXIMUM PEAK PULSE POWER	> 8 kW	> 12 kW	> 12 kW
BEAM QUALITY (M ²)	< 1.6	1.6 - 2	1.6 - 2
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1059 nm - 1065 nm	1059 nm - 1065 nm
MAXIMUM PULSE ENERGY	> 1.5 mJ	> 1 mJ	> 0.8 mJ
PULSE DURATION RANGE	12 ns - 1200 ns	3 ns - 2000 ns	2 ns - 500 ns
PULSE REPETITION FREQUENCY	1 kHz - 4000 kHz	1 kHz - 1000 kHz	1 kHz - 1000 kHz

STRUCTURAL DESIGN

DIMENSIONS (W X H X D)	447 mm x 417 mm x 88 mm	347 mm x 201 mm x 95 mm	347 mm x 201 mm x 95 mm
------------------------	-------------------------	-------------------------	-------------------------

INSTALLATION

AMBIENT TEMPERATURE	15 °C - 38 °C	0 °C - 45 °C	0 °C - 45 °C
---------------------	---------------	--------------	--------------

**TruPulse 4007 nano
(FK10-HS)****TruPulse 5020 nano
(FK10-EP)****LASER PARAMETERS**

AVERAGE OUTPUT POWER	70 W	200 W
MAXIMUM PEAK PULSE POWER	> 20 kW	> 50 kW
BEAM QUALITY (M ²)	2.5 - 3.5	4 - 6
WAVELENGTH SPECTRUM	1059 nm - 1065 nm	1061 nm - 1067 nm
MAXIMUM PULSE ENERGY	> 1.25 mJ	> 5 mJ
PULSE DURATION RANGE	10 ns - 250 ns	8 ns - 2000 ns
PULSE REPETITION FREQUENCY	1 kHz - 1000 kHz	1 kHz - 4000 kHz

STRUCTURAL DESIGN

DIMENSIONS (W X H X D)	377 mm x 249 mm x 95 mm	473 mm x 417 mm x 133 mm
------------------------	-------------------------	--------------------------

INSTALLATION

AMBIENT TEMPERATURE	0 °C - 40 °C	10 °C - 44 °C
---------------------	--------------	---------------