

TRUMPF



TruBend Series 5000

Technical data

TRUMPF



TruBend 5085**TruBend 5085 (S)****TruBend 5130**

PRESS FORCE	850 kN	850 kN	1300 kN
BENDING LENGTH	2210 mm	2720 mm	3230 mm
WIDTH BETWEEN COLUMNS	1750 mm	2260 mm	2690 mm
USABLE OPEN HEIGHT	385 mm	615 mm	385 mm
USABLE OPEN HEIGHT FOR EXTENDED VERSION (OPTION)	615 mm	-	615 mm
THROAT DEPTH	420 mm	420 mm	420 mm
USER INTERFACE	Touchpoint TruBend	Touchpoint TruBend	Touchpoint TruBend
MAXIMUM SPEED Y AXIS, OPERATION (OPTION)	25 mm/s	25 mm/s	25 mm/s
DIMENSIONS, WEIGHTS			
LENGTH	3020 mm	3530 mm	3980 mm
WIDTH	1800 mm	1800 mm	1900 mm
HEIGHT	2840 mm	2840 mm	2840 mm
WEIGHT	8300 kg	9100 kg	11800 kg

TruBend 5170**TruBend 5170 (S)****TruBend 5230**

PRESS FORCE	1700 kN	1700 kN	2300 kN
BENDING LENGTH	3230 mm	4250 mm	3230 mm
WIDTH BETWEEN COLUMNS	2690 mm	3680 mm	2690 mm
USABLE OPEN HEIGHT	615 mm	615 mm	615 mm
USABLE OPEN HEIGHT FOR EXTENDED VERSION (OPTION)	-	-	-
THROAT DEPTH	420 mm	420 mm	420 mm
USER INTERFACE	Touchpoint TruBend	Touchpoint TruBend	Touchpoint TruBend
MAXIMUM SPEED Y AXIS, OPERATION (OPTION)	25 mm/s	25 mm/s	25 mm/s
DIMENSIONS, WEIGHTS			
LENGTH	3980 mm	4970 mm	4150 mm
WIDTH	1900 mm	1900 mm	2055 mm
HEIGHT	3000 mm	3000 mm	3000 mm
WEIGHT	14150 kg	17850 kg	17200 kg

TruBend 5230 (S)**TruBend 5320**

PRESS FORCE	2300 kN	3200 kN
--------------------	---------	---------

TruBend 5230 (S)**TruBend 5320**

BENDING LENGTH 4250 mm 4420 mm

WIDTH BETWEEN COLUMNS 3680 mm 3680 mm

USABLE OPEN HEIGHT 615 mm 615 mm

USABLE OPEN HEIGHT FOR EXTENDED VERSION (OPTION) - -

THROAT DEPTH 420 mm 420 mm

USER INTERFACE Touchpoint TruBend Touchpoint TruBend

MAXIMUM SPEED Y AXIS, OPERATION (OPTION) 25 mm/s 25 mm/s

DIMENSIONS, WEIGHTS

LENGTH 5140 mm 5180 mm

WIDTH 2055 mm 2055 mm

HEIGHT 3000 mm 3200 mm

WEIGHT 19850 kg 23400 kg