



TruBend Series 8000

Technical data



TruBend 8230 (5 m)**TruBend 8320 (5 m)****TruBend 8400 (4 m)**

PRESS FORCE	2300 kN	3200 kN	4000 kN
BENDING LENGTH	5050 mm	5050 mm	4050 mm
WIDTH BETWEEN COLUMNS	4050 mm	4050 mm	3550 mm
THROAT DEPTH	420 mm	420 mm	420 mm
USER INTERFACE	T8000T multi-touch control	T8000T multi-touch control	T8000T multi-touch control
MAXIMUM Y PRESS OPERATION (OPTIONAL)	-	-	-
DIMENSIONS, WEIGHTS			
LENGTH	5990 mm	6010 mm	4950 mm
WIDTH	2160 mm	2160 mm	2160 mm
HEIGHT	3720 mm	3820 mm	3920 mm

TruBend 8500 (4 m)**TruBend 8600 (4 m)****TruBend 8800 (6 m)**

PRESS FORCE	5000 kN	6000 kN	8000 kN
BENDING LENGTH	4050 mm	4050 mm	6050 mm
WIDTH BETWEEN COLUMNS	3050 mm	3050 mm	5050 mm
THROAT DEPTH	420 mm	420 mm	420 mm
USER INTERFACE	T8000T multi-touch control	T8000T multi-touch control	T8000T multi-touch control
MAXIMUM Y PRESS OPERATION (OPTIONAL)	-	-	-
DIMENSIONS, WEIGHTS			
LENGTH	5090 mm	5130 mm	7170 mm
WIDTH	2360 mm	2460 mm	2760 mm
HEIGHT	4070 mm	3970 mm	4570 mm

TruBend 81000

PRESS FORCE	10000 kN
BENDING LENGTH	7050 / 8050 mm
WIDTH BETWEEN COLUMNS	6050 / 7050 mm
THROAT DEPTH	420 / 620 mm
USER INTERFACE	T8000T multi-touch control
MAXIMUM Y PRESS OPERATION (OPTIONAL)	8 mm/s
DIMENSIONS, WEIGHTS	

TruBend 81000

LENGTH	auf Anfrage mm
WIDTH	auf Anfrage mm
HEIGHT	auf Anfrage mm