



# TruTool S 250 18V LiHD rechargeable battery shear

Technical data

## TruTool S 250 18V LiHD rechargeable battery shear

### MAXIMUM SHEET THICKNESSES

|   |        |
|---|--------|
| MAXIMUM SHEET THICKNESS, STEEL 400 N/MM <sup>2</sup>          | 2.5 mm |
| MAXIMUM SHEET THICKNESS, STEEL 600 N/MM <sup>2</sup>          | 2 mm   |
| MAXIMUM SHEET THICKNESS, STEEL 800 N/MM <sup>2</sup>          | 1.5 mm |
| MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM <sup>2</sup> | 3 mm   |

### RADII

|                 |       |
|-----------------|-------|
| SMALLEST RADIUS | 20 mm |
|-----------------|-------|

### GENERAL

|                             |                   |
|-----------------------------|-------------------|
| WORKING SPEED               | 4 m/min - 7 m/min |
| STROKE RATE AT NOMINAL LOAD | 1300 1/min        |
| STROKE RATE DURING IDLE RUN | 1540 1/min        |
| STARTING HOLE DIAMETER      | 20 mm             |
| VOLTAGE                     | 18 V              |

### WEIGHT

|   |        |
|---|--------|
| WEIGHT (WITH 4 AH RECHARGEABLE BATTERY) | 2.6 kg |
|---|--------|