



# TruFiber

Technical data

**TruFiber 500****TruFiber 1000****TruFiber 1500****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	500 W	1000 W	1500 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	15 W - 500 W with active power regulation	30 W - 1000 W with active power regulation	45 W - 1500 W with active power regulation
WAVELENGTH	1075 nm ± 7 nm	1075 nm ± 7 nm	1075 nm ± 7 nm
DIAMETER OF LASER LIGHT CABLE	26 µm	26 µm	26 µm
LENGTH OF THE LASER LIGHT CABLE	-	-	10 m
BEAM QUALITY			

**STRUCTURAL DESIGN**

DIMENSIONS, COMPACT VERSION (W X H X D)	448 mm x 568 mm x 705 mm	448 mm x 568 mm x 705 mm	448 mm x 568 mm x 896 mm
DIMENSIONS, STAND ALONE VERSION (W X H X D)	600 mm x 1600 mm x 850 mm	600 mm x 1600 mm x 850 mm	-
MAXIMUM NUMBER OF LASER LIGHT CABLES	1	1	1

**INSTALLATION**

AMBIENT TEMPERATURE	5 °C - 45 °C	5 °C - 45 °C	5 °C - 45 °C
---------------------	--------------	--------------	--------------

**TruFiber 2000****TruFiber 2000 New Generation****LASER PARAMETERS**

LASER POWER ON THE WORKPIECE	2000 W	2000 W
TYPICAL POWER CONSTANCY AT RATED POWER	± 1 % with active power regulation	± 1 % with active power regulation
CONTINUOUSLY ADJUSTABLE POWER RANGE	60 W - 2000 W with active power regulation	60 W - 2000 W with active power regulation
WAVELENGTH	1075 nm ± 7 nm	1075 nm ± 7 nm
DIAMETER OF LASER LIGHT CABLE	26 µm	50 µm
LENGTH OF THE LASER LIGHT CABLE	10 m	20 m
BEAM QUALITY		2.1 mm ■ mrad

**STRUCTURAL DESIGN**

DIMENSIONS, COMPACT VERSION (W X H X D)	448 mm x 568 mm x 896 mm	448 mm x 568 mm x 896 mm
DIMENSIONS, STAND ALONE VERSION (W X H X D)	-	-
MAXIMUM NUMBER OF LASER LIGHT CABLES	1	1

**INSTALLATION**

AMBIENT TEMPERATURE	5 °C - 45 °C	5 °C - 45 °C
---------------------	--------------	--------------