



# TruBend Series 8000

Technical data



**TruBend 8230 (5 m)****TruBend 8320 (5 m)****TruBend 8400 (4 m)**

<b>PRESS FORCE</b>	2300 kN	3200 kN	4000 kN
<b>BENDING LENGTH</b>	5050 mm	5050 mm	4050 mm
<b>WIDTH BETWEEN COLUMNS</b>	4050 mm	4050 mm	3550 mm
<b>THROAT DEPTH</b>	420 mm	420 mm	420 mm
<b>USER INTERFACE</b>	T8000T multi-touch control	T8000T multi-touch control	T8000T multi-touch control
<b>MAXIMUM Y PRESS OPERATION (OPTIONAL)</b>	-	-	-
<b>DIMENSIONS, WEIGHTS</b>			
LENGTH	5990 mm	6010 mm	4950 mm
WIDTH	2160 mm	2160 mm	2160 mm
HEIGHT	3720 mm	3820 mm	3920 mm

**TruBend 8500 (4 m)****TruBend 8600 (4 m)****TruBend 8800 (6 m)**

<b>PRESS FORCE</b>	5000 kN	6000 kN	8000 kN
<b>BENDING LENGTH</b>	4050 mm	4050 mm	6050 mm
<b>WIDTH BETWEEN COLUMNS</b>	3050 mm	3050 mm	5050 mm
<b>THROAT DEPTH</b>	420 mm	420 mm	420 mm
<b>USER INTERFACE</b>	T8000T multi-touch control	T8000T multi-touch control	T8000T multi-touch control
<b>MAXIMUM Y PRESS OPERATION (OPTIONAL)</b>	-	-	-
<b>DIMENSIONS, WEIGHTS</b>			
LENGTH	5090 mm	5130 mm	7170 mm
WIDTH	2360 mm	2460 mm	2760 mm
HEIGHT	4070 mm	3970 mm	4570 mm

**TruBend 81000**

<b>PRESS FORCE</b>	10000 kN
<b>BENDING LENGTH</b>	7050 / 8050 mm
<b>WIDTH BETWEEN COLUMNS</b>	6050 / 7050 mm
<b>THROAT DEPTH</b>	420 / 620 mm
<b>USER INTERFACE</b>	T8000T multi-touch control
<b>MAXIMUM Y PRESS OPERATION (OPTIONAL)</b>	8 mm/s
<b>DIMENSIONS, WEIGHTS</b>	

## TruBend 81000

LENGTH	auf Anfrage mm
WIDTH	auf Anfrage mm
HEIGHT	auf Anfrage mm